

## The connector with lateral fixing for hook - Solar profile connection or profiles Solar cross connection (90° degrees)



Profiles solar cross connection



Detail: cross connector

### VERSIONS

- cross connector XC in aluminium alloy AW6060 T6 according to EN 755-2:2013
- hexagon socket cylindrical head screw TCEI in stainless steel A2-70 according to EN ISO 3506-1:2009
- channel nut FCN AL in aluminium alloy AW6060 T66 according to EN 755-2:2013 and nylon PA6 grey

### ADVANTAGES

- Fast: quick Solar profile installation by tightening 1 screw.
- Complete: the pre-assembled cross connector PXC does not need any further accessory (e.g. screws, washers, nuts).
- Safe fixing: the cross connector XC has a large contact surface area that increases the connection load-bearing capacity.

### APPLICATIONS

- Suitable for:**
- Special application System
- For the connection of:**
- Profile Solar-fish
  - Profile Solar-mid

### FUNCTIONING

**Hook - profile Solar connection:**

- Connect the cross connector XC to the hook GT/GTR/GTT/GTP/GTPR/GC using hex head screw SKS M 8 and hexagonal nut MU M 8 included in the hook package.
- Approach the profile Solar to the cross connector XC hook.
- Lock the connection tightening the hexagon socket cylindrical head screw TCEI, applying the right installation torque (10 Nm).


**Crossed connection:**

- Connect the cross connector XC to the lower Solar profile, upper channel, using the channel nut FCN AL M 8 and screw SKS M 8; rotate it clockwise 90°.
- Approach the upper Solar profile to the cross connector XC/PXC hook.
- Lock the connection tightening the hexagon socket cylindrical head screw TCEI, applying the right installation torque (10 Nm).

## TECHNICAL DATA



Cross connector **XC AL**




Item	Art.-No.	Weight	Thread	Screw length	Sales unit	GTIN (EAN code)
		W [g]	M	l [mm]	[pcs]	
<b>XC AL</b>	<b>516998</b>	40	M 8	20	10	8001132031834

## TECHNICAL DATA



Pre-assembled cross connector **PXC**



Item	Art.-No.	Weight	Thread	Screw length	Installation torque	Sales unit	GTIN (EAN code)
		W [g]	M	l [mm]	T <sub>inst</sub> [Nm]	[pcs]	
<b>PXC</b>	<b>522671</b>	65	M 8	20	10	10	8001132031681

## ACCESSORIES



Hexagon socket cylindrical head screw **TCEI A2**



Channel nut **FCN AL**

Item	Art.-No.	Weight	Thread	Screw length	Width across nut	Sales unit	GTIN (EAN code)
		W [g]	M	l [mm]	○SW	[pcs]	
<b>TCEI M 8 x 20 mm A2</b>	<b>071984</b>	-	M 8	20	6	50	8001132719848
<b>FCN AL M 8</b>	<b>571165</b>	10	M 8	-	-	50	8001132711651